



Hydraulic Hose - No Skive

Pilot Hose

Construction

- Tube : Oil resistant Synthetic Rubber
- Reinforcement : One braide of high tensile steel wire
- Cover : Black colour, Oil, weather and abrasion resistant Synthetic Rubber

Application and Temperature Range

- Petroleum base hydraulic fluids and lubricating oils within a temperature range of -40°F to +212°F (-40°C to +100°C)
- Water, Water / Glycol and Water / Oil emulsion hydraulic fluids up to +185°F (+85°C)

Size		I.D.		O.D.		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Dash	DN	inch	mm	inch	mm	PSI	in bar	PSI	in bar	mm	inch
4	6	1/4	6.4	0.47	12.0	1,500	120	6,000	480	30	1,2
6	10	3/8	9.5	0.63	16.0	1,500	120	6,000	480	50	2,0



Thermoplastic Hose

Sewer Jetting Hose

Construction

- Tube : Thermoplastic Elastomer
- Reinforcement : Single or double braid of polyester / aramid fibre
- Cover : Polyurethane, green colour. Special colours and private print upon request.

Application and Temperature Range

- Standard Sewer Cleaning vehicles and Sewer Cleaning equipment. Special fully bonded construction and optimum cut and wear resistance, for an increased lifetime. Cover resistant to microbiological degradation. Lightweight compared to conventional rubber sewer cleaning hoses. Available in customary length.
- Temperature standards: -40°F to +212°F (-40°C to +100°C)

Size		I.D.		O.D.		Working Pressure		Min. Burst Pressure		Min. Bend Radius	
Dash	DN	inch	mm	inch	mm	PSI	in bar	PSI	in bar	mm	inch
8	12	1/2	12.7	0.92	23.4	4,000	280	12,000	840	75	3,0
12	20	3/4	19.1	1.15	29.2	3,600	250	9,000	625	125	5,0
16	25	1	25.4	1.50	37.9	3,600	250	9,000	625	160	6,4
20	32	1 1/4	32.0	1.80	45.7	3,600	250	9,000	625	250	10,0