

## AIR HOSE 40 BAR (Hi-Temperature Wire Reinforced)

**UNIGAWA® AIR HOSE 40 BAR**



Black Blue

### Common Applications

Heavy duty hot air hose for use specifically on drill rigs for high pressure, high temperature applications.

### Tube

Black, SBR / NR rubber, heat and oil mist resistant.

### Reinforcement

Multi-ply of steel wire cords.

### Cover

Blue or Black SBR / EPDM rubber, wrapped surface, abrasion and weather resistant.

### Branding

With Black / White **UNIGAWA®** printing.

### Temperature Range

- 25°C to + 135°C.

### Safety Factor

3 : 1



**AIR**

**UNIGAWA®** Industrial Rubber Hose

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M <sup>3</sup> (30 Mt)	Coil Length Mt
RAD 7025	1	25.4	38.0	40 / 120	0.94	0.073	30/60
RAD 7032	1 1/4	32.0	45.0	40 / 120	1.14	0.107	30/60
RAD 7038	1 1/2	38.0	55.5	40 / 120	2.13	0.133	30/60
RAD 7050	2	50.8	68.5	40 / 120	2.72	0.268	30/60
RAD 7065	2 1/2	63.5	81.0	40 / 120	3.28	0.401	30/60
RAD 7075	3	76.2	95.0	40 / 120	4.05	0.544	30/60
RAD 7100	4	101.6	125.5	40 / 120	7.13	1.116	30/60

• Other sizes, colours and lengths available on request.