



**AIR**

## COMPRESSED AIR HOSE (complies to ISO 2398)



■ Red   
 ■ Green   
 ■ Blue   
 ■ Black

### Common Applications

Heavy duty air supply line. Ideal for good performance in workshop and hire industries.

#### Tube

Black, SBR / NBR rubber, Oil mist resistant.

#### Reinforcement

High strength synthetic polyester braided.

#### Cover

Green, Blue, Red & Black, SBR / CR rubber, smooth surface, oil mist and weather resistant.

#### Branding

With **UNIGAWA®** White printing.

#### Temperature Range

- 25°C to + 70°C.

#### Safety Factor

4 : 1



UNIGAWA® Industrial Rubber Hose

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume	Coil Length
	inch	mm	mm	Bar	Kg/Mt	M <sup>3</sup>	Mt
RAD 10006	1/4	6.4	13.0	16 / 64	0.17	0.028	100
RAD 10008	5/16	8.0	15.0	16 / 64	0.21	0.035	100
RAD 10010	3/8	9.5	17.0	16 / 64	0.26	0.043	100
RAD 10013	1/2	12.7	22.0	16 / 64	0.42	0.077	100
RAD 10016	5/8	16.0	26.0	16 / 64	0.55	0.107	100
RAD 10019	3/4	19.0	29.0	16 / 64	0.63	0.130	100
RAD 10025	1	25.4	36.0	16 / 64	0.85	0.195	100

• Other sizes, colours and lengths available on request.