



GENERAL PURPOSE DISCHARGE HOSE (EPDM)



Common Applications

Softwall hose designed to handle a wide range of chemical products, acids and bases. It is specially recommended to convey industrial waters and for usage in water purification systems.

Tube

Black, smooth, EPDM rubber.

Reinforcement

High strength synthetic cord incorporating anti-static wire.

Cover

Black, smooth (wrapped finish), EPDM rubber, resistance to chemical products, abrasion, weather and ozone.

Branding

With Green/Black **UNIGAWA®** stripe.

Temperature Range

- 40°C to + 100°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RCD 3019	3/4	19.0	30.0	10 / 30	0.62	0.043	30 / 60
RCD 3025	1	25.4	37.0	10 / 30	0.86	0.068	30 / 60
RCD 3032	1 1/4	32.0	44.0	10 / 30	1.05	0.104	30 / 60
RCD 3038	1 1/2	38.0	52.0	10 / 30	1.45	0.153	30 / 60
RCD 3050	2	50.8	66.0	10 / 30	2.02	0.260	30 / 60

- Other sizes, colours and lengths available on request.