



XLPE CHEMICAL DISCHARGE HOSE

Cross-linked polyethylene tube



Common Applications

Softwall hose with cross-linked polyethylene tube, suitable for handling a wide range of chemicals, petroleum products, and oils.

Tube

Black, smooth, cross-linked polyethylene (XLPE).

Reinforcement

High strength synthetic cord and anti-static copper wire

Cover

Green (wrapped finish), EPDM rubber with excellent resistance to abrasion, weather and ozone.

Branding

With Orange/Black **UNIGAWA®** stripe.

Temperature Range

- 30°C to + 93°C (120°C for 30 minutes)

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RCD 2019	3/4	19.0	30.0	16 / 48	0.60	0.037	30 / 60
RCD 2025	1	25.4	37.0	16 / 48	0.81	0.068	30 / 60
RCD 2032	1 1/4	32.0	44.0	16 / 48	1.02	0.104	30 / 60
RCD 2038	1 1/2	38.0	52.0	16 / 48	1.41	0.133	30 / 60
RCD 2050	2	50.8	66.0	16 / 48	1.99	0.268	30 / 60
RCD 2065	2 1/2	63.5	80.0	16 / 48	2.65	0.342	30 / 60
RCD 2075	3	76.2	94.0	16 / 48	3.43	0.529	30 / 60
RCD 2100	4	101.6	120.0	16 / 48	5.01	1.080	30 / 60

- Other sizes, colours and lengths available on request.