

FOOD DELIVERY HOSE *Fatty foods*



FOOD

Common Applications

Softwall hose for delivery of food products, particularly suitable for oily and fatty foods.

(Max 110°C for a few minutes with steam; max 30°C for a few minutes with 1% peracetic acid, 2% phosphoric acid, 5% caustic soda.)

Tube

White, smooth, F.D.A. approved NBR rubber.

Reinforcement

High strength synthetic cord.

Cover

Blue (wrapped finish), NBR rubber, fat and ageing resistant.

Branding

With Purple/Black **UNIGAWA®** stripe.

Temperature Range

- 35°C to + 80°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RFD 2019	3/4	19.0	30.0	10 / 30	0.60	0.037	30 / 60
RFD 2025	1	25.4	37.0	10 / 30	0.83	0.068	30 / 60
RFD 2032	1 1/4	32.0	44.0	10 / 30	1.02	0.104	30 / 60
RFD 2038	1 1/2	38.0	52.0	10 / 30	1.41	0.133	30 / 60
RFD 2050	2	50.8	66.0	10 / 30	1.96	0.268	30 / 60

- Other sizes, colours and lengths available on request.