

FOOD SUCTION & DELIVERY HOSE *Non-fatty food liquids*



FOOD

Common Applications

Hardwall hose for suction and delivery of water, wine, juice, soft drinks, and other foodstuffs when a food quality hose is required. Not recommended for oily or fatty liquids.

(Max 110°C for a few minutes with steam; max 30°C for a few minutes with 1% peracetic acid, 2% phosphoric acid, 5% caustic soda.)

Tube

White, smooth, F.D.A. approved EPDM rubber.

Reinforcement

High strength synthetic cord and helix wire

Cover

Oxred, (wrapped finish), EPDM rubber, weather resistance.

Branding

With Purple/White **UNIGAWA**® stripe.

Temperature Range

- 35°C to + 100°C.

Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M ³	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(30 Mt)	Mt
RFS 1025	1	25.4	37.0	10 / 30	0.96	0.068	30 / 60
RFS 1032	1 1/4	32.0	44.0	10 / 30	1.15	0.094	30 / 60
RFS 1038	1 1/2	38.0	51.0	10 / 30	1.48	0.133	30 / 60
RFS 1050	2	50.8	65.0	10 / 30	2.12	0.268	30 / 60
RFS 1065	2 1/2	63.5	79.0	10 / 30	2.89	0.342	30 / 60
RFS 1075	3	76.2	92.0	10 / 30	3.51	0.507	30 / 60
RFS 1100	4	101.6	120.0	10 / 30	5.33	1.080	30 / 60

• Other sizes, colours and lengths available on request.

UNIGAWA® Industrial Rubber Hose