

TWIN-LINE WELDING HOSE

UNIGAWA® TWIN WELDING HOSE (OXY) W/P 20 BAR

UNIGAWA® TWIN WELDING HOSE (ACY) W/P 20 BAR

 Red/Blue

 Red/Green

Common Applications

Dual extruded medium pressure hose is suitable for the transfer of oxygen and acetylene gas for welding and gas cutting applications.

Tube

Black SBR / NR rubber.

Reinforcement

High strength synthetic polyester braided.

Cover

Blue / Red / Green, SBR / EPDM rubber, smooth surface rubber, abrasion and weather resistant.

Branding

With **UNIGAWA®** Black printing.

Temperature Range

- 20°C to + 70°C.

Safety Factor

3 : 1



Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M³	Coil Length Mt
RGD 4005	3/16 + 3/16	5.0	12.0	20 / 60	0.33	0.041	100
RGD 4006	1/4 + 1/4	6.3	13.0	20 / 60	0.36	0.059	100
RGD 4008	5/16 + 5/16	8.0	15.0	20 / 60	0.44	0.073	100
RGD 4010	3/8 + 3/8	9.5	16.0	20 / 60	0.52	0.083	100

• Other sizes, colours and lengths available on request.



GAS

UNIGAWA® Industrial Rubber Hose