

## HOT WATER DISCHARGE HOSE



### Common Applications

Designed to convey hot water, fluids even slightly acidic and non-aggressive in chemical industries.

#### Tube

Black EPDM rubber compound.

#### Reinforcement

High strength synthetic cord.

#### Cover

Black, ageing, ozone, weather resistant, EPDM rubber compound.

#### Branding

With Blue/Yellow **UNIGAWA**<sup>®</sup> stripe.

#### Temperature Range

- 30°C to + 93°C.

#### Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M <sup>3</sup>	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(30 Mt)	Mt
RSD 2013	1/2	12.7	23.0	20 / 60	0.35	0.029	30 / 60
RSD 2016	5/8	16.0	26.0	20 / 60	0.42	0.035	30 / 60
RSD 2019	3/4	19.0	29.0	20 / 60	0.48	0.043	30 / 60
RSD 2025	1	25.4	37.0	20 / 60	0.82	0.068	30 / 60
RSD 2032	1 1/4	32.0	44.0	20 / 60	0.94	0.104	30 / 60
RSD 2038	1 1/2	38.0	52.0	20 / 60	1.26	0.133	30 / 60
RSD 2050	2	50.8	66.0	20 / 60	1.75	0.268	30 / 60

• Other sizes, colours and lengths available on request.



**HOT**

**UNIGAWA**<sup>®</sup> Industrial Rubber Hose