

## MUD SUCTION & DELIVERY HOSE



MATERIAL HANDLING

### Common Applications

Hardwall hose for used for the suction of sand and gravel mixed with water in construction operations.

#### Tube

Black, smooth, SBR / NR rubber, with good resistance to abrasion and lacerations.

#### Reinforcement

High strength synthetic cord plus steel helix wire.

#### Cover

Black, (wrapped finish), SBR rubber, resistant to weathering and abrasion.

#### Branding

**UNIGAWA**<sup>®</sup> stripe.

#### Temperature Range

- 40°C to + 70°C.

#### Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume	
	inch	mm	mm	Bar	Kg/Mt	M <sup>3</sup> (30 Mt)	
RHS 4075	3	76.2	94.0	17 / 51	3.47	0.530	30 / 60
RHS 4100	4	101.6	122.0	17 / 51	5.35	1.116	30 / 60
RHS 4125	5	127.0	150.0	17 / 51	7.26	2.287	30 / 60
RHS 4150	6	152.4	180.0	17 / 51	12.58	2.764	30 / 60
RHS 4200	8	203.2	233.0	17 / 51	15.43	5.948	30 / 40

- Other sizes, colours and lengths available on request.

**UNIGAWA**<sup>®</sup> Industrial Rubber Hose