

## ANTI-STATIC OIL HOSE



### Common Applications

Heavy Duty Anti-static Oil Hose suited for the transfer of diesel and petroleum based products.

#### Tube

Black NBR rubber, oil resistant.

#### Reinforcement

High strength of synthetic polyester braided incorporating an anti-static copper wire.

#### Cover

Black NBR PVC rubber, smooth surface, weather & oil resistant.

#### Branding

With **UNIGAWA®** White printing.

#### Temperature Range


- 20°C to + 80°C.

#### Safety Factor

3 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume	Coil Length
	inch	mm	mm	Bar	Kg/Mt	M <sup>3</sup>	Mt
RPD 3006	1/4	6.3	15.0	20 / 60	0.20	0.035	100
RPD 3008	5/16	8.0	16.0	20 / 60	0.21	0.040	100
RPD 3010	3/8	9.5	18.0	20 / 60	0.26	0.052	100
RPD 3013	1/2	12.7	22.0	20 / 60	0.36	0.082	100
RPD 3016	5/8	16.0	26.0	20 / 60	0.46	0.107	100
RPD 3019	3/4	19.0	30.0	20 / 60	0.59	0.132	100
RPD 3022	7/8	22.0	33.0	20 / 60	0.66	0.130	60
RPD 3025	1	25.4	37.0	20 / 60	0.80	0.135	60
RPD 3032	1 1/4	32.0	44.0	20 / 60	1.02	0.085	30
RPD 3038	1 1/2	38.0	53.0	20 / 60	1.50	0.141	30

• Other sizes, colours and lengths available on request.



PETROLEUM

UNIGAWA® Industrial Rubber Hose