

BUNKERING HOSE 10 BAR (Complies to EN1765 type S10)



Common Applications

Hardwall hose used for the suction and discharge of petroleum products from tankers and barges, bunkering service and industrial applications; suitable for aromatic content up to 50%. Available with swaged-on fittings or built-in fittings.

Tube

Black, smooth, synthetic rubber, suitable for aromatic content up to 50%.

Reinforcement

High strength synthetic cord, steel helix wire and anti-static copper wire.

Cover

Black, smooth (wrapped finish), synthetic rubber resistant to weather, oil and sea water.

Branding

With Brown/White **UNIGAWA®** stripe.

Temperature Range

- 20°C to + 82°C.

Electrical characteristics

Electrically continuous.

Safety Factor

4 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RPS 3075	3	76.2	94.0	10 / 40	3.65	0.530	30 / 60
RPS 3100	4	101.6	124.0	10 / 40	5.99	1.116	30 / 60
RPS 3150	6	152.4	182.0	10 / 40	11.84	2.764	30 / 40
RPD 3200	8	203.2	235.0	10 / 40	17.08	5.948	30 / 60

- Other sizes, colours and lengths available on request.