


FUEL HOSE



PETROLEUM

Common Applications

Designed for use in fuel line systems for the transfer of petroleum product under low pressure.

Tube

Black NBR rubber, oil resistant.

Reinforcement

High strength synthetic polyester braided.

Cover

Black NBR / EPDM rubber, smooth surface, heat & mid oil resistant.

Branding

With **UNIGAWA®** Black printing.

Temperature Range

- 20°C to + 80°C.

Safety Factor

3 : 1

Product Code	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³	Coil Length Mt
RPD 2004	4.0	10.0	10 / 30	0.09	0.022	100
RPD 2005	5.0	11.0	10 / 30	0.11	0.022	100
RPD 2006	6.0	12.0	10 / 30	0.12	0.024	100
RPD 2007	7.0	13.0	10 / 30	0.13	0.028	100
RPD 2008	8.0	14.0	10 / 30	0.15	0.033	100
RPD 2009	9.0	15.0	10 / 30	0.16	0.035	100
RPD 2010	10.0	16.0	10 / 30	0.17	0.040	100
RPD 2011	11.0	17.0	10 / 30	0.19	0.043	100
RPD 2012	12.0	19.0	10 / 30	0.24	0.053	100
RPD 2013	13.0	20.0	10 / 30	0.26	0.061	100
RPD 2014	14.0	21.0	10 / 30	0.27	0.070	100
RPD 2016	16.0	24.0	10 / 30	0.36	0.093	100

• Other sizes, colours and lengths available on request.

UNIGAWA® Industrial Rubber Hose