

## **FUEL-OIL DELIVERY HOSE** (Complies to EN1765 type L15)



### **Common Applications**

Softwall hose used for transferring petroleum products from tankers, barges, and other industrial applications, suitable for aromatic content up to 50%; supplied with built in or swaged on fittings.

#### **Tube**

Black, smooth, synthetic rubber, suitable for aromatic content up to 50%.

#### **Reinforcement**

High strength synthetic cord plus anti-static copper wires.

#### **Cover**

Black, smooth (wrapped finish), synthetic rubber, resistant to weather, oil and sea water.

#### **Branding**

With Brown/Black **UNIGAWA®** stripe.

#### **Temperature Range**


- 20°C to + 82°C.

#### **Safety Factor**

4 : 1

Product Code	Nominal	I.D.	O.D.	Working/Burst Pressure	Weight	Volume M <sup>3</sup>	Coil Length
	inch	mm	mm	Bar	Kg/Mt	(30 Mt)	Mt
RPD 7050	2	50.8	68.0	15 / 60	2.30	0.268	30 / 60
RPD 7065	2½	63.5	82.0	15 / 60	3.07	0.386	30 / 60
RPD 7075	3	76.2	96.0	15 / 60	3.92	0.544	30 / 60
RPD 7100	4	101.6	124.0	15 / 60	5.66	1.116	30 / 60
RPD 7150	6	152.4	177.0	15 / 60	9.23	2.831	30 / 60
RPD 7200	8	203.2	230.0	15 / 60	13.32	5.695	30 / 40

• Other sizes, colours and lengths available on request.



**PETROLEUM**

**UNIGAWA®** Industrial Rubber Hose