

ULTRA WATER DISCHARGE HOSE



Common Applications

Heavy duty mandrel built hose is suitable for transfer of sea water, waste water and light slurry solutions in both high and low pressure applications.

Tube

Black SBR / EPDM rubber.

Reinforcement

Piles of high strength polyester cord.

Cover

Black SBR / EPDM rubber, wrapped surface, abrasion and weather resistant.

Branding

With Blue/Black **UNIGAWA®** stripe.

Temperature Range

- 20°C to + 80°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RWD 2025	1	25.4	37.0	20 / 60	0.93	0.068	30 / 60
RWD 2032	1 1/4	32.0	44.0	20 / 60	1.14	0.104	30 / 60
RWD 2038	1 1/2	38.0	52.0	20 / 60	1.57	0.133	30 / 60
RWD 2050	2	50.8	66.0	20 / 60	2.19	0.268	30 / 60
RWD 2065	2 1/2	63.5	80.0	20 / 60	2.95	0.350	30 / 60
RWD 2075	3	76.2	94.0	20 / 60	3.81	0.529	30 / 60
RWD 2100	4	101.6	122.0	20 / 60	5.58	1.080	30 / 60
RWD 2150	6	152.4	175.0	20 / 60	9.21	2.482	30 / 60

• Other sizes, colours and lengths available on request.