



WATER

UNIGAWA® Industrial Rubber Hose

ULTRA WATER SUCTION HOSE



Common Applications

A Heavy duty suction hose is suitable for use in agriculture, construction and mining industries. This hose is suitable for water, sea water, waste water and light slurry transfer in both negative and positive pressure applications.

Tube

Black SBR / NR rubber.

Reinforcement

Piles of high strength polyester cord incorporating a steel helix wire.

Cover

Black, SBR / EPDM rubber, wrapped surface, abrasion and weather resistant.

Branding

With Blue/White **UNIGAWA®** stripe.

Temperature Range

- 30°C to + 80°C.

Safety Factor

3 : 1

Product Code	Nominal inch	I.D. mm	O.D. mm	Working/Burst Pressure Bar	Weight Kg/Mt	Volume M ³ (30 Mt)	Coil Length Mt
RWS 2050	2	50.8	65.0	20 / 60	2.32	0.260	30 / 60
RWS 2065	2 1/2	63.5	79.0	20 / 60	2.75	0.342	30 / 60
RWS 2075	3	76.2	92.0	20 / 60	3.85	0.507	30 / 60
RWS 2100	4	101.6	122.0	20 / 60	6.45	1.080	30 / 60
RWS 2150	6	152.4	178.0	20 / 60	11.83	2.673	30 / 60
RWS 2200	8	203.2	230.0	20 / 60	16.72	5.847	30 / 40

- Other sizes, colours and lengths available on request.