

## TSD 'STANDARD' SCREW CLAMPS



The TSD standard screw clamps offer many possible uses. They are designed to be used in conjunction with ratchet lever hoists to align steel structures or fabrications. They are ideally suited for the construction industry.

The unique design of the spindle makes it easy to attach to 'angle' plate. This is achieved by simply turning the handle which applies the pressure to the plate holding it securely.

**NB.** The plate surface of the material to be lifted must not exceed a hardness level of HRC 30/Brinell 300.



Model	WLL kgs*	Jaw capacity mm	Weight kgs*
TSD 1500	1500	0 - 35	5
TSD 3000	3000	0 - 35	8
TSD 5000	5000	0 - 40	16
TSD 7500	7500	0 - 40	19.5


\*Per clamp. • Please contact our sales team for full technical drawings.

## TSZ 'TWO WAY' SCREW CLAMPS



The TSZ 'two way' screw clamps have all the same features of the TSD (shown above) but have the additional benefit of a second lifting point enabling it to pull in two different directions

**NB.** The plate surface of the material to be lifted must not exceed a hardness level of HRC 30/Brinell 300.



Model	WLL kgs*	Jaw capacity mm	Weight kgs*
TSZ 500	500	0 - 28	3
TSZ 1500	1500	0 - 35	5
TSZ 3000	3000	0 - 35	9
TSZ 5000	5000	0 - 40	16
TSZ 7500	7500	0 - 40	21

\*Per clamp. • Please contact our sales team for full technical drawings.

## TSH 'SWIVEL HOOK' SCREW CLAMPS



The TSH 'swivel hook' screw clamps offer many possible applications. It is particularly useful for lifting, transferring and pulling sheet metal, girders and steel constructions.

The clamps are supplied complete with an alloy safety shackle, that allows for pulling in 180° degrees.

**NB.** The plate surface of the material to be lifted must not exceed a hardness level of HRC 30/Brinell 300.



Model	WLL kgs*	Jaw capacity mm	Weight kgs*
TSH 750	750	0 - 30	3.1
TSH 1500	1500	0 - 32	7
TSH 3000	3000	0 - 50	11
TSH 5000	5000	0 - 80	27

\*Per clamp. • Please contact our sales team for full technical drawings.